


SERIES: MD-XXPL100 | **DESCRIPTION:** MINI DIN CONNECTOR

FEATURES

- panel mount
- 10cm lead wires
- 3~8 pins



PART NUMBER KEY




SPECIFICATIONS

| parameter | conditions/description | min | typ | max | units |
|-----------------------|-------------------------|-----|-----------|--------|------------|
| rated input voltage | | | 100 12 | | Vac Vdc |
| rated input current | at 100 Vac at 12 Vdc | | | 1 2 | A A |
| contact resistance | | | | 30 | mΩ |
| insulation resistance | at 250 Vdc | 50 | | | MΩ |
| voltage withstand | for 1 minute | | | 250 | Vac |
| insertion force | | 1 | | 4.5 | kg |
| withdrawl force | | 0.8 | | 3 | kg |
| operating temperature | | -40 | | 85 | °C |
| life | | | 1,000 | | cycles |



MECHANICAL DRAWINGS

units: mm[inches]

TOLERANCE: ± 0.2 mm



| | MATERIAL | PLATING |
|-------------------------|-----------------|---------|
| earth terminal | brass | tin |
| contact terminals (1~8) | phosphor bronze | tin |
| wire | AWG #26 | |
| plastic | PBT | |








MD-30PL100

MD-40PL100

MD-50PL100

MD-60PL100

MD-80PL100



| PIN | Wire Color | Wire Color | Wire Color | Wire Color | Wire Color |
|-----|------------|------------|------------|------------|------------|
| 1 | black | black | brown | brown | brown |
| 2 | green | green | black | white | white |
| 3 | orange | yellow | green | black | black |
| 4 | | red | yellow | green | blue |
| 5 | | | red | yellow | green |
| 6 | | | | red | yellow |
| 7 | | | | | orange |
| 8 | | | | | red |

REVISION HISTORY

| rev. | description | date |
|------|----------------------|------------|
| 1.0 | initial release | 02/23/2006 |
| 1.01 | new template applied | 03/07/2012 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.