


APPARATUS TYPE			Exchange surface (m <sup>2</sup> )	CAPACITY (l)		INDUSTRIAL VERSION		B	C	MAXIMUM ADMISSIBLE TEMPERATURE (°C)		
"Narrow" baffles spacing	"Medium" baffles spacing	"Wide" baffles spacing		SHELL side	TUBES side	A	Empty weight (kg)			MAXIMUM ADMISSIBLE PRESSURE (bar)		
AL07SFQ2AA	AL07MFQ2AA		0.74	1.6	1.6	363.7	13.0	160	114	With " nitrile " gaskets 100		
AL08SFQ2AA		AL08LFQ2AA	0.90	2.0	1.8	417.7	13.9	214	168	With " viton " gaskets 150		
AL09SFQ2AA	AL09MFQ2AA	AL09LFQ2AA	1.10	2.4	2.0	482.7	15.0	279	233	MAXIMUM ADMISSIBLE PRESSURE (bar)		
AL10SFQ2AA	AL10MFQ2AA	AL10LFQ2AA	1.33	2.9	2.2	559.7	16.3	356	310	Working	Testing	16
AL11SFQ2AA	AL11MFQ2AA	AL11LFQ2AA	1.61	3.6	2.5	652.7	17.8	449	403			
AL12SFQ2AA	AL12MFQ2AA	AL12LFQ2AA	1.95	4.3	2.9	764.7	19.7	561	515	SHELL side	16	24
AL13SFQ2AA	AL13MFQ2AA	AL13LFQ2AA	2.36	5.2	3.3	898.7	22.0	695	649			
AL14SFQ2AA	AL14MFQ2AA	AL14LFQ2AA	2.84	6.3	3.8	1059.7	24.7	856	810	TUBES side	10	15
AL15SFQ2AA	AL15MFQ2AA	AL15LFQ2AA	3.42	7.6	4.4	1251.7	27.9	1048	1002			
AL16SFQ2AA	AL16MFQ2AA	AL16LFQ2AA	4.12	9.1	5.1	1483.7	31.8	1280	1234			
AL17SFQ2AA	AL17MFQ2AA	AL17LFQ2AA	4.96	11.0	6.0	1761.7	36.5	1558	1512			



11 rue Pasteur - BP 8  
F-78601 MAISONS-LAFFITTE CEDEX  
Tél.: +33 (0) 1 39 62 06 56 - Fax: +33 (0) 9 82 63 67 02  
info@picker.fr - www.picker.fr

Manufacturing according to PICKER standard PED 97/23/CE SHELL side / TUBES side = Article 3 §3 / Article 3 §3

External painting = Primer paint colour grey RAL 7046

HEAT EXCHANGERS

## AL (07 to 17) .FQ2AA

Industrial version with fluid "four passages" on TUBES side

FORMAT A4	CODE N° G. POHU / P4988GB.DWG	PRODUCT DATA SHEET N° <b>P4988 GB</b>	REV 1
--------------	----------------------------------	--	----------

THIS DOCUMENT MAY BE MODIFIED WITHOUT NOTICE

SCALE	WITHOUT	DATE	23/07/15	SHEET	1 OF 1
-------	---------	------	----------	-------	--------