



The dimensions for completely assembled QUADRA-FLEX® Type SC Spacer Couplings are shown below. See next page for dimensions of separate components.

Coupling Size	Required Distance Between Shafts	Use Flange Number	Use Hub Number	Max. Bore Standard Keyway	Dimensions				Weight ² (Kg.) [•]
					D	L ²	G	R	
4JSC	88,9	4JSC35	4H	28,6	62,5	142,9	15,9	12,7	2,13
5SC	88,9	5SC35	5H	28,6	82,6	142,9	19,1	14,3	1,86
6SC	88,9	6SC35	6H	34,9	101,6	149,2	22,2	19,1	3,22
6SC	111,1	6SC44	6H	34,9	101,6	171,5	22,2	19,1	3,58
6SC	127,0	6SC50	6H	34,9	101,6	187,3	22,2	19,1	3,86
7SC	88,9	7SC35	7H	41,3	117,5	161,9	25,4	15,9	4,13
7SC	111,1	7SC44	7H	41,3	117,5	184,2	25,4	15,9	4,58
7SC	127,0	7SC50	7H	41,3	117,5	200,0	25,4	15,9	4,85
8SC	88,9	8SC35	8H	47,6	138,4	174,6	28,6	20,6	6,67
8SC	88,9	8SC35-10	10H★	60,3	138,4	206,4	28,6	20,6	10,30
8SC	111,1	8SC44	8H	47,6	138,4	196,9	28,6	20,6	7,30
8SC	127,0	8SC50	8H	47,6	138,4	212,7	28,6	30,2	7,21
8SC	127,0	8SC50-10	10H★	60,3	138,4	244,5	28,6	30,2	12,02
9SC	88,9	9SC35	9H★	54,0	161,3	190,5	36,5	27,0	9,98
9SC	111,1	9SC44	9H★	54,0	161,3	209,6	36,5	27,0	10,62
9SC	127,0	9SC50	9H★	54,0	161,3	225,4	36,5	27,0	11,16
9SC	127,0	9SC50-11	11H★	73,0	161,3	263,5	36,5	30,2	18,24
9SC	177,8	9SC70-11	11H★	73,0	161,3	314,3	36,5	30,2	21,87
9SC	196,9	9SC78-11	11H★	73,0	161,3	333,4	36,5	30,2	23,05
10SC	120,7	10SC48	10H★	60,3	190,5	238,1	41,3	30,2	16,06
10SC	127,0	10SC50	10H★	60,3	190,5	244,5	41,3	30,2	17,33
10SC	177,8	10SC70-13	13H★	85,7	190,5	346,1	41,3	47,6	32,58
10SC	196,9	10SC78-13	13H★	85,7	190,5	365,1	41,3	47,6	34,30
10SC	254,0	10SC100-13	13H★	85,7	190,5	422,3	41,3	47,6	40,38
11SC	120,7	11 SC48	11H★	73,0	219,1	269,9	47,6	30,2	24,73
11SC	127,0	11 SC50	11H★	73,0	219,1	263,5	47,6	30,2	24,86
11SC	177,8	11SC70-14	14H	98,4	219,1	371,5	47,6	50,8	38,88
11SC	196,9	11SC78-14	14H	98,4	219,1	390,5	47,6	50,8	40,88
11SC	254,0	11SC100-14	14H	98,4	219,1	447,7	47,6	50,8	46,51
12SC	177,8	12SC70	12H★	73,0	254,0	327,0	58,7	38,1	39,79
12SC	177,8	12SC70-14	14H	98,4	254,0	371,5	58,7	50,8	44,87
12SC	196,9	12SC78	12H★	73,0	254,0	346,1	58,7	38,1	41,52
12SC	196,9	12SC78-14	14H	98,4	254,0	390,5	58,7	50,8	46,87
12SC	254,0	12SC100-14	14H	98,4	254,0	447,7	58,7	50,8	52,40
13SC	196,9	13SC78	13H★	85,7	298,5	365,1	68,3	47,6	55,26
14SC	196,9	14SC78	14H	98,4	352,4	390,5	82,6	50,8	81,40

Dimensions in millimeters unless otherwise specified.

★ Short (HS) hub also available.

• Approximate weight for completely assembled spacer coupling.

¹ 4JSC35 x 28,6 has a shallow keyway.

² "L" dimension and weight will change if one or two short (HS) hubs are used.

NOTE: Refer to page C-43 to order — specify components separately.